R

PIN INSTALLATION TECHNOLOGY

Model DP Drilling and Pinning Machine

This self contained vertical drilling and pinning machine is ideally suited for moderate to high production applications that require accurate drilling and pinning of assemblies. The concept of drilling and pinning with one system eliminates tight tolerance and precision drilling of individual components to ensure proper alignment of holes for assembly. The Model DP machine consists of an automatic highprecision drilling unit, a SPIROL Model CR Pin Insertion Machine and a precision air-powered linear slide unit to move the assembly between the drill unit and installation station.

The Model DP operates as follows: the assembly is loaded into a custom fixture nest, and the machine is activated. The assembly is automatically clamped, advances to the drilling position and the hole is drilled. The assembly then slides back to the loading/pinning position, and the pin is automatically installed. The fixture un-clamps and the completed assembly is manually removed.

Design Features/Benefits:

Precise:

- Drill guide bushing to support and guide drill bit during drilling operation
- Drill pecking feature for straight, accurate holes
- Fine pin insertion depth adjustment
- Precision ground machine table
- Critical components are dowelled in place to maintain alignment

Built to Last:

- Recirculating flood coolant in the drilling operation for drill bit life and chip removal
- Cushioned cylinder return stroke to reduce shock and noise
- Hardened pin guide bushings and hard coated vibratory feeder bowl

Versatile:

- Allen Bradley Panel View Human Machine Interface for programming and control of all machine functions
- Can be easily configured to accommodate a variety of applications
- Capable of both wet and dry drilling operation
- Hole sizes from 0.8mm (1/32") to 6mm (1/4") diameter
- Capable of insertion forces up to 1,800 lbs.

Efficient:

- Eliminate the need to handle components multiple times through several different processes
- Automatic operation of drilling and pinning processes
- Automatic feed, delivery and insertion of pins
- Collet style drill chuck, with internal stop for quick no-measurement drill replacement Full perimeter guarding with electrically interlocked access door for operator safety
- Safe: Infrared light curtain option readily available







Application: Gear to Shaft Assembly for Hydraulic Pump

A leading manufacturer of hydraulic pumps required a method to permanently affix various sized gears to shafts. The gears were bronze, and the shafts were 400 series stainless steel. After press fitting the gears into position, they would drill a hole partially through the assembly, install a heavy duty SPIROL® Coiled Spring **Pin**, and stake the entrance point for maximum security. Prior to SPIROL's involvement, this process was done manually using 3 different stations. SPIROL offered to consolidate all operations into one complete installation machine. Since the customer offered many different gear/shaft assembly sizes, the machine needed to be versatile enough to accommodate the 11 existing assemblies, as well as be able to handle new variations as designed. Tooling changeover had to be quick and simple, with little to no machine adjustment. The cycle time had to be less than a minute, and drill bits were expected to last at least 500 cycles.

The **SPIROL** Model **DP** machine consists of a standard Model CR Pin Insertion machine, an automatic, production quality, highprecision drilling unit, and a precision air-powered linear slide unit to move the assemblies between the drill unit and installation/ staking station.

SPIROL's solution provides a machine cycle time of 45 seconds. drill bits yield 600 plus parts, and tooling change-over takes less than 15 minutes between assemblies. This machine doubled the previous production output, and provided a payback of less than 12 months.

SPIROL offers complimentary Application Engineering support! We will assist on new designs as well as help resolve issues, and recommend cost savings on existing designs. Let us help by visiting Application Engineering Services on SPIROL.ca.

Technical Centres

Americas SPIROL Canada

3103 St. Etienne Boulevard Windsor Ontario N8W 5B1 Canada Tel. +1 519 974 3334

Fax. +1 519 974 6550

SPIROL International Corporation

30 Rock Avenue

Danielson, Connecticut 06239 U.S.A. Tel. +1 860 774 8571

Fax +1 860 774 2048

SPIROL Shim Division

321 Remington Road Stow, Ohio 44224 U.S.A. Tel. +1 330 920 3655

Fax. +1 330 920 3659

SPIROL Mexico

Avenida Avante #250 Parque Industrial Avante Apodaca Apodaca, N.L. 66607 Mexico Tel. +52 81 8385 4390

Fax. +52 81 8385 4391

SPIROL Brazil

Rua Mafalda Barnabé Soliane, 134 Comercial Vitória Martini, Distrito Industrial CEP 13347-610, Indaiatuba, SP, Brazil

Tel. +55 19 3936 2701 Fax. +55 19 3936 7121

Europe SPIROL United Kingdom

17 Princewood Road Corby, Northants NN17 4ET United Kingdom Tel: +44 (0) 1536 444800 Fax: +44 (0) 1536 203415

SPIROL France

Cité de l'Automobile ZAC Croix Blandin 18 Rue Léna Bernstein 51100 Reims, France Tel: +33 (0) 3 26 36 31 42 Fax: +33 (0) 3 26 09 19 76

SPIROL Germany

Ottostr. 4 80333 Munich, Germany Tel: +49 (0) 89 4 111 905 71 Fax: +49 (0) 89 4 111 905 72

SPIROL Spain

Plantes 3 i 4 Gran Via de Carles III 84 08028, Barcelona, Spain Tel/Fax: +34 932 71 64 28

SPIROL Czech Republic

Evropská 2588 / 33a 160 00 Prague 6-Dejvice Czech Republic Tel: +420 226 218 935

SPIROL Poland

ul. Solec 38 lok. 10 00-394, Warsaw, Poland Tel. +48 510 039 345

Pacific

Asia SPIROL Asia Headquarters

1st Floor, Building 22, Plot D9, District D No. 122 HeDan Road

Wai Gao Qiao Free Trade Zone Shanghai, China 200131 Tel: +86 (0) 21 5046-1451 Fax: +86 (0) 21 5046-1540

SPIROL Korea

16th Floor, 396 Seocho-daero, Seocho-gu, Seoul, 06619, South Korea Tel: +82 (0) 10 9429 1451

e-mail: info-ca@spirol.com

SPIROL.ca